



HANDICAP SPACES
 MINIMUM 12' WIDE
 WITHIN 200' OF ENTRANCE
 WALKS UNINTERRUPTED, NO STEPS
 AT LEAST TWO SPACES
 UP TO 400 SPACES SHALL HAVE 2% HANDICAP
 MORE THAN 400 SPACES SHALL HAVE EIGHT
 SPACES PLUS 1% FOR HANDICAP

OFFSTREET PARKING

A	A	B	A+B	C	D	E	F	G	H	A ₁	C ₁
ANGLE OF PARKING	DEPTH OF STALL	ASILE WIDTH	-----	WIDTH OF BAY	CURB LENGTH	WIDTH OF STALL	LENGTH OF STRIPE	WASTE SPACE	DEPTH OF OVERHANG	DEPTH OF STALL	WIDTH OF AREA
0°	8.5	12	20.5	29.0	24.0	-----	-----	-----	-----	-----	-----
45°	19.5	13	32.5	52.0	12.0	8.5	27.5	19.5	3.0	16.5	46.0
60°	20.8	18	38.8	59.6	9.8	8.5	24.0	12.0	2.1	18.7	55.4
90°	19.0	24.0	43.0	62.0	8.5	8.5	19.0	-----	-----	-----	-----

STANDARD DETAIL 209